

# Rubber In A Can

## Safety Data Sheet



### SECTION 1: Product and company identification

Product name : Rubber In A Can  
Use of the substance/mixture : Aerosol  
Coating  
Product code : 800201  
Company : Share Corporation  
P.O. Box 245013  
Milwaukee, WI 53224 - USA  
T (414) 355-4000  
Emergency number : Chemtrec: (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Aerosol 1 H222  
Liquefied gas H280  
Skin Irrit. 2 H315  
Eye Dam. 1 H318  
Carc. 2 H351  
Repr. 2 H361  
STOT SE 3 H336  
STOT RE 2 H373  
Asp. Tox. 1 H304

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: Extremely flammable aerosol  
Contains gas under pressure; may explode if heated  
May be fatal if swallowed and enters airways  
Causes skin irritation  
Causes serious eye damage  
May cause drowsiness or dizziness  
Suspected of causing cancer  
Suspected of damaging fertility or the unborn child  
May cause damage to organs (central nervous system, eye, kidneys, liver, Skin, respiratory system) through prolonged or repeated exposure

Precautionary statements (GHS-US)

: Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Keep away from heat, sparks, open flames, hot surfaces. Do not smoke. - No smoking  
Do not spray on an open flame or other ignition source  
Pressurized container: Do not pierce or burn, even after use  
Do not breathe dust, fume, gas, mist, spray, vapors  
Avoid breathing mist, spray  
Wash thoroughly after handling  
Use only outdoors or in a well-ventilated area  
Wear protective gloves, eye protection  
If swallowed: Immediately call a doctor, a POISON CENTER, Do NOT induce vomiting  
If on skin: Wash with plenty of IF ON SKIN: Wash with plenty of soap and water  
If inhaled: Remove person to fresh air and keep comfortable for breathing  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If exposed or concerned: Get medical advice/attention  
Immediately call a POISON CENTER, a doctor  
Call a POISON CENTER, a doctor if you feel unwell  
Get medical advice/attention if you feel unwell  
Specific treatment (see First aid measures on this label)  
Do NOT induce vomiting  
If skin irritation occurs: Get medical advice/attention  
Take off contaminated clothing and wash before reuse

# Rubber In A Can

## Safety Data Sheet



Store in a well-ventilated place. Keep container tightly closed  
 Store locked up  
 Protect from sunlight. Store in a well-ventilated place  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
 Dispose of contents/container to comply with local/regional/national/international regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Limestone	(CAS No) 1317-65-3	30 - 40	Not classified
toluene	(CAS No) 108-88-3	10 - 20	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
methyl acetate	(CAS No) 79-20-9	10 - 20	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
acetone, propan-2-one, propanone	(CAS No) 67-64-1	1 - 10	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
xylene	(CAS No) 1330-20-7	0.1 - 1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
solvent naphtha(petroleum),light aliphatic	(CAS No) 64742-89-8	0.1 - 1	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified, [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 165 °C to 290 °C (330 °F to 554 °F).]	(CAS No) 64742-94-5	0.1 - 1	Asp. Tox. 1, H304
carbon black	(CAS No) 1333-86-4	0.1 - 1	Carc. 2, H351

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Artificial respiration and/or oxygen if necessary. Respiratory problems: consult a doctor/medical service.
- First-aid measures after skin contact : Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Irritation of the respiratory tract. Causes skin irritation. Causes serious eye irritation. Causes damage to organs through prolonged or repeated exposure.
- Symptoms/injuries after inhalation : Harmful if inhaled. May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



# Rubber In A Can

## Safety Data Sheet



### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Adapt extinguishing media to the environment.
- Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread. Contact with water liberates flammable gases.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable aerosol. Under fire conditions closed containers may rupture or explode.
- Explosion hazard : Contains gas under pressure; may explode if heated. Vapors may travel long distances along ground before igniting/flashing back to vapor source.

#### 5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate unnecessary personnel. Isolate from fire, if possible, without unnecessary risk. Gas is denser than air. May accumulate in low areas e.g. close to the ground.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Do not enter without an appropriate protective equipment. Do not breathe gas/vapor.
- Emergency procedures : Avoid contact with eyes. NO open flames, NO sparks, and NO smoking.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

#### 6.2. Environmental precautions

- Prevent entry to sewers and public waters. Do not allow to enter drains or water courses. Stop leak if safe to do so.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so. Eliminate every possible source of ignition. Collect spillage.
- Methods for cleaning up : Take up liquid spill into inert absorbent material.

#### 6.4. Reference to other sections

- No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.
- Precautions for safe handling : Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not breathe vapors. Wear personal protective equipment. Observe normal hygiene standards. Take precautionary measures against static discharge.
- Hygiene measures : Remove contaminated clothes. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Do not puncture, incinerate or crush.
- Storage conditions : Store locked up. Keep container tightly closed. Protect from sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Heat-ignition : KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.
- Storage area : Store in a cool area. Store in a dry area. Store away from heat. Aerosol 2. Store in a well-ventilated place.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

toluene (108-88-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Visual impair; female repro;
acetone, propan-2-one, propanone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm

# Rubber In A Can

## Safety Data Sheet



<b>acetone, propan-2-one, propanone (67-64-1)</b>		
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
<b>xylene (1330-20-7)</b>		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
<b>methyl acetate (79-20-9)</b>		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
ACGIH	Remark (ACGIH)	eye & URT irr
<b>carbon black (1333-86-4)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (Carbon black; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction)

### 8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Personal protective equipment : Gloves. Safety glasses. Protective clothing. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol. Opaque. Black.
Odor	: Solvent-like odour
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: -156 °F Based on propellant
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.037 g/ml
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: < 20 cSt
Viscosity, dynamic	: No data available
VOC content	: 22.5 %



# Rubber In A Can

## Safety Data Sheet



### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

#### 10.4. Conditions to avoid

No flames, No sparks. Eliminate all sources of ignition. Extremely high or low temperatures. Direct sunlight.

#### 10.5. Incompatible materials

None known.

#### 10.6. Hazardous decomposition products

No additional information available

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>xylene (1330-20-7)</b>	
LC50 inhalation rat (ppm)	4550 ppmV/4h
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (gases)	4550.000 ppmV/4h
ATE CLP (dust, mist)	1.500 mg/l/4h

<b>carbon black (1333-86-4)</b>	
LD50 oral rat	> 8000 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	> 3000 mg/kg (Rabbit)

Skin corrosion/irritation : Causes skin irritation.  
 Serious eye damage/irritation : Causes serious eye damage.  
 Respiratory or skin sensitization : Not classified  
 Germ cell mutagenicity : Not classified.  
 Carcinogenicity : Suspected of causing cancer.

<b>toluene (108-88-3)</b>	
IARC group	3 - Not Classifiable

<b>xylene (1330-20-7)</b>	
IARC group	3 - Not Classifiable

<b>carbon black (1333-86-4)</b>	
IARC group	2B - Possibly Carcinogenic to Humans

Reproductive toxicity : Suspected of damaging fertility or the unborn child.  
 Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.  
 Specific target organ toxicity (repeated exposure) : May cause damage to organs (central nervous system, eye, kidneys, liver, Skin, respiratory system) through prolonged or repeated exposure.  
 Aspiration hazard : May be fatal if swallowed and enters airways.  
 Symptoms/injuries after inhalation : Harmful if inhaled. May cause respiratory irritation.  
 Symptoms/injuries after skin contact : Causes skin irritation.  
 Symptoms/injuries after eye contact : Causes serious eye irritation.  
 Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.  
 Likely routes of exposure : Skin and eyes contact.;Inhalation;Ingestion.

### SECTION 12: Ecological information

#### 12.1. Toxicity

<b>carbon black (1333-86-4)</b>	
LC50 fish 1	> 1000 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio)

# Rubber In A Can

## Safety Data Sheet



carbon black (1333-86-4)	
EC50 Daphnia 1	> 5600 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 24 h; Daphnia magna; Static system; Fresh water)
LC50 fish 2	1000 mg/l (LC0; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 1	> 10000 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)

### 12.2. Persistence and degradability

carbon black (1333-86-4)	
Persistence and degradability	Biodegradability: not applicable. Biodegradability in soil: not applicable. Adsorbs into the soil.
ThOD	Not applicable

### 12.3. Bioaccumulative potential

carbon black (1333-86-4)	
Bioaccumulative potential	Not bioaccumulative.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container to comply with local/regional/national/international regulations. This material and its container must be disposed of as hazardous waste.

Additional information : Do not re-use empty containers.

## SECTION 14: Transport information

### Department of Transportation (DOT)

#### Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306.

### ADR

No additional information available

### Transport by sea

UN-No. (IMDG) : UN1950  
 Proper Shipping Name (IMDG) : Aerosols, Flammable  
 Class (IMDG) : 2.1 - Flammable gases

### Air transport

UN-No. (IATA) : UN1950  
 Proper Shipping Name (IATA) : Aerosols, Flammable  
 Class (IATA) : 2.1 - Gases : Flammable

## SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

toluene	CAS No 108-88-3	10 - 20
xylene	CAS No 1330-20-7	0.1 - 1

toluene (108-88-3)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
acetone, propan-2-one, propanone (67-64-1)	
Not listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
xylene (1330-20-7)	



# Rubber In A Can

## Safety Data Sheet



xylene (1330-20-7)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

### SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Liquefied gas	Gases under pressure Liquefied gas
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.*