

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-300 (R) FOAM BOARD ADHESIVE
MSDS Number: P74300145
Version Number 3
Revision Date: OCT-13-2005
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: PL-300 (R) FOAM BOARD ADHESIVE
HMIS Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPE: B

Company Identification: HENKEL CONSUMER ADHESIVES
7405 PRODUCTION DRIVE
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800)321-0253
Information phone/Fax: (440) 255-8900 / (440) 974-8358
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)
(800) 424-9300
in Canada CANUTEC 613-996-6666

Product Class ADHESIVE
Trade Name PL Brands
Product Code _____

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
Light Hydrotreated Naphtha	64742-49-0	15 - 25	Y
SILICA, QUARTZ	14808-60-7	TRACE	Y

Ingredient Notes:
Remaining ingredients are not considered OSHA hazardous.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Non-sag mastic
Appearance/Color: Light blue
Solubility (in water): insoluble
pH Value, +/- .3: Not Applicable
Boiling Range: 135.°F - 165.°F (57.22°C - 73.89°C)
Vapor Pressure (mmHg): over 99. @ 68.°F (20.°C)
Evaporation Rate: 5.5 times Faster than n-Butyl Acetate

Vapor Density: Heavier than air

% Volatile, Weight approx. 20.%
% Volatile, Volume approx. 40.%

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-300 (R) FOAM BOARD ADHESIVE
MSDS Number: P74300145
Version Number 3
Revision Date: OCT-13-2005
Page Number: 2

Specific Gravity: 1.366
VOC (less H2O or exempt) 280 g/l, 19%

NOTE:

*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

SECTION IV - FIRE FIGHTING MEASURES (Flash,UEL,LEL for solvent only)

Flammability Class IB
Flash Range: approx.
0.°F - 5.°F (-17.78°C - -15.°C)
Tag Closed Cup
Explosive Range (LEL/UEL): 1.%
6.7%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam
Use water fog to cool material in vicinity of fire.

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
operated in pressure demand with full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may rupture when exposed to extreme heat.
Solvent vapors are heavier than air and travel along the ground.
Vapors given off are flammable and may be ignited in air explosively.

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY:

ENTRY THROUGH

Inhalation? YES | Skin? YES | Ingestion? YES

Contains N-Hexane (110-54-3) in trace quantities, which can
cause peripheral neuropathy & nervous system damage.

CARCINOGENICITY...

NTP? N/E | IARC Monographs? N/E | OSHA? NO

EFFECTS OF OVEREXPOSURE

Eyes: Can cause irritation, redness, tearing and blurred vision.
Skin: Prolonged or repeated contact can cause moderate
irritation, defatting, and dermatitis.
Inhalation: May cause nose or throat irritation. High concen-
trations may cause acute central nervous system depression
characterized by headaches, dizziness, nausea and confusion.
Ingestion: Can cause gastrointestinal irritation, nausea,
vomiting and diarrhea.

FIRST AID MEASURES

Eyes: Flush eyes gently with water for at least 15 minutes

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-300 (R) FOAM BOARD ADHESIVE
MSDS Number: P74300145
Version Number 3
Revision Date: OCT-13-2005
Page Number: 3

lifting eyelids occasionally; get prompt medical attention
Skin: Wash thoroughly with soap and water; apply a mild skin cream.
Remove contaminated clothing.
Inhalation: Move affected person to fresh air; if breathing is
difficult, administer oxygen; if breathing has stopped,
give artificial respiration. Get medical attention.
Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

CHRONIC HAZARDS

NOTICE: Reports have associated repeated and prolonged
occupational overexposure to solvents with permanent brain,
nervous system, liver or kidney damage or may cause cardiac
arrhythmia. INTENTIONAL misuse of this product by
deliberately inhaling its vapors may be harmful or fatal.
SILICA: Normal use of this product does not produce dust. Sanding dried
material could generate trace amounts of Silica (quartz) which
is a suspect human carcinogen (IARC group 1).
Repeated and prolonged occupational overexposure to Crystalline
Silica may cause silicosis, a progressively disabling lung disease.

SECTION VI - STABILITY AND REACTIVITY

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATABILITY:

Keep away from strong oxidizing agents.

CONDITIONS TO AVOID:

Keep away from heat, spark, open flames and any ignition source.

HAZARDOUS DECOMPOSITION PRODUCTS:

Will produce fumes and smoke containing carbon monoxide and
dioxide under fire conditions.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

STEPS TO BE TAKEN IN CASE OF SPILL:

Eliminate all ignition sources. Ventilate confined areas.
(Open windows and doors). Wear appropriate protective clothing.
Cover with absorbent. Scoop into sealable safety container.

WASTE DISPOSAL METHOD:

Dispose of following local, state, and federal regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-300 (R) FOAM BOARD ADHESIVE
MSDS Number: P74300145
Version Number: 3
Revision Date: OCT-13-2005
Page Number: 4

Light Hydrotreated Naphtha
400.00 PPM N/est N/est N/est 400.00 PPM

SILICA, QUARTZ
0.05 mg/F3 N/est N/est N/est 0.10 mg/M3

Note: The TLV for Silica is for the respirable fraction of dust only.

RESPIRATORY PROTECTION:

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV.
Ventilate during application and curing of this product.

PROTECTIVE CLOTHING:

Rubber gloves should be worn where skin contact is likely.
Wear impervious clothing and shoes.

EYE PROTECTION:

Chemical goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat, spark and flame.
Keep out of reach of children.
Keep container closed while not in use.
Do not cut or burn recepticals that have contained a solvent based product. Do not reuse this container.
Use only in a well ventilated area.

N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

SECTION IX - TRANSPORT INFORMATION: (not all sizes available)

GROUND TRANSPORT (DOT) - DOMESTIC

Units less than 5L (1.3 gallons liquid) i.e. 10oz, 28oz, 1 gal.

Proper Shipping Name: CONSUMER COMMODITY
Classification: ORM-D
DOT Label Required: ORM-D
Shipping Document: CONSUMER COMMODITY, ORM-D
ERG Code: 171

Units GREATER than 5L i.e. 5 gal. pail

Proper Shipping Name: ADHESIVE
Classification: CLASS 3

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-300 (R) FOAM BOARD ADHESIVE
MSDS Number: P74300145
Version Number: 3
Revision Date: OCT-13-2005
Page Number: 5

DOT Label Required: Flammable Liquid, UN1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PGIII,
for 50 gal. drum use PG II
ERG Code: 128

AIR TRANSPORT (DOT) - DOMESTIC

Units less than 5L (1.3 gallons liquid) i.e. 10oz, 28oz, 1gal.

Proper Shipping Name: CONSUMER COMMODITY
Classification: ORM-D
DOT Label Required: ORM-D-AIR
Shipping Document: Consumer Commodity, ORM-D
ERG Code: 171

Units GREATER than 5L i.e. 5 gal. pail

Proper Shipping Name: ADHESIVE
Classification: Class 3
DOT Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PG III,
for 50 gal. drum use PG II
ERG Code: 128

AIR TRANSPORT (IATA) - INTERNATIONAL

Units less than 5L (1.3 gallons liquid) i.e. 10oz, 28oz, 1 gal.

Proper Shipping Name: CONSUMER COMMODITY
Classification: class 9
Label Required: ID8000
Shipping Document: Consumer Commodity, 9, ID8000
ERG Code: 9L

Units GREATER than 5L i.e. 5 Gal. pail, 50 gal. drum

Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PGIII,
for 50 gal. drum use PG II
ERG Code: 3L

MARINE - OCEAN TRANSPORT (IMDG)

Units less than 5L (1.3 gallons liquid) i.e. 10oz, 28oz, 1 gal.

Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN1133, Class 3, Ltd. Qty.
(on Ocean container only, not required on cartons)
Shipping Document: ADHESIVE, 3, UN1133, PG III, LTD.QTY.
EMS Code: F-E, S-D

MATERIAL SAFETY DATA SHEET

MSDS Name: PL-300 (R) FOAM BOARD ADHESIVE
MSDS Number: P74300145
Version Number 3
Revision Date: OCT-13-2005
Page Number: 6

Units GREATER than 5L i.e. 5 gal. pail, 50 gal drum
Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PGI, III,
for 50 gal. drum use PG II
EMS Code: F-E, S-D

SECTION X - REGULATORY INFORMATION:

-PROP 65 (CARCINOGEN)

WARNING: This product contains a chemical known to the state of California to cause cancer.

Ingredient Name	CAS Number	Percent
SILICA, QUARTZ	14808-60-7	TRACE

SARA Section 311/312 Hazard Categories met: Fire Hazard, Immediate (Acute) and Delayed (Chronic) Health Hazards.

Chemical ingredients are listed on the TSCA inventory.
SARA Section 313 toxic chemicals: NONE above the de minimis reporting thresholds.

DISCLAIMER:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.