

MATERIAL SAFETY DATA SHEET

EMALLOY CO. INC.

P.U. BOX 350

BRYN MAWR, PA 19010-0350

Telephone: (610) 527-3700

(610) 527-3878 Fax No.:

CHEMICAL NAME:

COMMON/TRADE NAME:

DATE:

SUPERSEDES:

Titanium Dioxide Leucoxene, Rutile Rutile "94", TiO2

October 1, 2012

October 1, 2009

Distributed by: Laguna Clay Company 14400 Lomitas Ave City of Industry, CA 91746

1-800-4Laguna info@lagunaclay.com www.lagunaclay.com

ECTION I - H	AZARDOUS INC	REDIENTS
--------------	--------------	----------

Hazardous Components (Specific Chemical Identity)	CAS#	OSHA PEL	ACGIH TLV
Titanium Dioxide	13463-67-7	10mg/M3 TWA (Total Dust)	10mg/M³ TWA
Silicon Dioxide	14808-60-7	0.lmg/M³ TWA (Respirable Dust)	0.025mg/M ³ TWA (Respirable Fraction)
Zirconium Silicate	14940-68-2	5mg/M ³ TWA, 10mg/M ³ STEL (as Zr)	5mg/M ³ TWA, 10mg/M ³ STEL (as Zr)

SECTION II -	PHYSICAL	CHEMICAL	CHARACTERISTICS
SECTION II	LUISIONE	CHEMICAL	UNADAU ENIO I IUO

Melting Point

Approx. 3000° F

Specific Gravity (H₂O = 1)

No odor.

4.3 to 5.0

(Water) Nil

Other

oppearance and Odor

Black to brownish red luster.

SECTION III — REACTIVITY DATA

Stability: Unstable Conditions to Avoid

Stable X

Incompatibility (Materials to Avoid)

None known.

Hazardous Decomposition or Byproducts

None known.

Hazardous Polymerization:

May Occur

Conditions to Avoid

Will Not Occur

SECTION IV — FIRE AND EXPLOSION HAZARD DATA

]

Flash Point (Method Used)

None.

Extinguishing Media

Special Fire Fighting Procedures

Not a fire or explosion hazard.

Unusual Fire and Explosion Hazards

Laguna Clay Company

www.Lagunaclay.com

1-800-4Laguna info@Lagunaclay.com

C-78 (1/87)

(OVER)

SECTION V - HEALTH HAZARD DATA

Route(s) of Entry

Inhalation.

Health Hazards (Acute and Chronic)

May cause irritation of the respiratory system. Longtime overexposure may cause silicosis (lung damage) due to silica content. This product contains approximately 1% crystalline silica (common sand), small amounts of which may be in respirable form and may cause cancer if longtime overexposure exists.

Carcinogenicity

Crystalline silica (common sand) has been listed by the International Agency for Research on Cancer as a human carcinogen. NIOSH has classified Titanium Dioxide as a carcinogen based on an experimental animal study, but U.S. OSHA and the American Conference Governmental Industrial Hygienists (ACGIH) have found insufficient evidence to list it as such.

Signs and Symptoms of Overexposure

Irritation of the respiratory system.

Emergency and First Aid Procedures On contact with skin, practice proper hygiene. On contact with eyes, flush eyes thoroughly for 15 minutes. On inhalation of excessive dust, move to fresh air. Seek medical attention if problems persist.

SECTION VI — SPECIAL PROTECTION AND PRECAUTIONS

Ventilation and Engineering Controls

Appropriate ventilation.

Personal Protective Equipment

NIOSH-certified respirator, gloves and ANSI-approved

eye protection.

Safe Handling, Use and Storage

Normal handling and storage.

Protective Measures During Repair & Maintenance

Use protective equipment listed above.

Other

SECTION VII — SPILL OR LEAK PROCEDURES

Steps to Be Taken in Case Material is Released or Spilled Use normal clean-up procedure.

Waste Disposal Method

Follow federal, state and local regulations.

Other Precautions

Follow all other precautions and data noted herein.

NOTE: The data contained in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information herein is based on technical data that Chemalloy believes to be reliable. It is intended to be used by persons with technical skill. Prior to use, users shall conduct their own investigation(s) to determine the suitability of the information for their particular purpose, and appropriate warnings and safe handling procedures should be provided to handlers and users. Any use of this data must be determined by the user to be in accordance with federal, state and local laws and regulations. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents. Since conditions of use and suitability are beyond Chemalloy's control, any risks of use and suitability are therefore assumed by the user, and Chemalloy expressly disclaims all warranties, including warranties of merchantability and fitness for a particular purpose, express or implied, in respect to the use or suitability of the material.