

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	KLEAN HEAT	
Company Name:	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	Phone Number: (901)775-0100
Web site address:	www.wmbarr.com	
Emergency Contact:	3E 24 Hour Emergency Contact	(800)451-8346
Information:	W.M. Barr Customer Service	(800)398-3892
Intended Use:	Heater Fuel	
Synonyms:	GKKH99991, GKKHDP, GKKHDPL	
Additional Information	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.	

2. HAZARDS IDENTIFICATION

- Flammable Liquids, Category 4**
- Acute Toxicity: Inhalation, Category 4**
- Skin Corrosion/Irritation, Category 2**
- Serious Eye Damage/Eye Irritation, Category 2B**
- Specific Target Organ Toxicity (single exposure), Category 3**
- Aspiration Toxicity, Category 1**




GHS Signal Word:	Danger
GHS Hazard Phrases:	H227: Combustible liquid. H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H320: Causes eye irritation. H332: Harmful if inhaled. H336: May cause drowsiness or dizziness.
GHS Precaution Phrases:	P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P261: Avoid breathing gas/mist/vapors/spray. P264: Wash hands thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection. P235: Keep cool.
GHS Response Phrases:	P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P302+352: IF ON SKIN: Wash with plenty of soap and water. P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312: Call a POISON CENTER or doctor/physician if you feel unwell. P321: Specific treatment see label. P331: Do NOT induce vomiting. P332+313: If skin irritation occurs, get medical advice/attention.

SAFETY DATA SHEET

KLEAN HEAT

GHS Storage and Disposal Phrases:	P337+313: If eye irritation persists, get medical advice/attention. P362: Take off contaminated clothing and wash before re-use. P370+378: In case of fire, use dry chemical powder to extinguish. P403+233: Store container tightly closed in well-ventilated place. P405: Store locked up. P501: Dispose of contents/container to local, state and federal regulations.												
Hazard Rating System:	<table border="1" style="border-collapse: collapse; text-align: center;"> <tr><td style="background-color: #0000FF; color: white;">HEALTH</td><td style="width: 20px;"> </td><td style="width: 20px;">1</td></tr> <tr><td style="background-color: #FF0000; color: white;">FLAMMABILITY</td><td> </td><td>2</td></tr> <tr><td style="background-color: #FFA500; color: white;">PHYSICAL</td><td> </td><td>0</td></tr> <tr><td style="background-color: #FFFFFF; color: black;">PPE</td><td> </td><td>B</td></tr> </table>	HEALTH		1	FLAMMABILITY		2	PHYSICAL		0	PPE		B
HEALTH		1											
FLAMMABILITY		2											
PHYSICAL		0											
PPE		B											
HMIS:	<table border="1" style="border-collapse: collapse; text-align: center;"> <tr><td style="background-color: #0000FF; color: white;">HEALTH</td><td style="width: 20px;"> </td><td style="width: 20px;">1</td></tr> <tr><td style="background-color: #FF0000; color: white;">FLAMMABILITY</td><td> </td><td>2</td></tr> <tr><td style="background-color: #FFA500; color: white;">PHYSICAL</td><td> </td><td>0</td></tr> <tr><td style="background-color: #FFFFFF; color: black;">PPE</td><td> </td><td>B</td></tr> </table>	HEALTH		1	FLAMMABILITY		2	PHYSICAL		0	PPE		B
HEALTH		1											
FLAMMABILITY		2											
PHYSICAL		0											
PPE		B											
OSHA Regulatory Status:	This material is classified as hazardous under OSHA regulations.												
Potential Health Effects (Acute and Chronic):	Eye contact : May cause eye irritation. Inhalation : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach. Skin contact : Causes skin irritation.												
Inhalation:	Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness												
Skin Contact:	Adverse symptoms may include the following: irritation redness												
Eye Contact:	Adverse symptoms may include the following: pain or irritation watering redness												
Ingestion:	Adverse symptoms may include the following: nausea or vomiting												



3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
64742-47-8	Hydrotreated light distillate (petroleum)	100.0 %	OA5504000

4. FIRST AID MEASURES

Emergency and First Aid Procedures:	<p>Inhalation: If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.</p> <p>Skin contact: Wash with soap and large quantities of water for at least 15 minutes. Seek medical attention if irritation from contact persists.</p> <p>Eye contact: Immediately flush eyes with water, remove any contact lens, continue flushing with water for at least 15 minutes. Get medical attention.</p> <p>Ingestion: Do not induce vomiting. Call your poison control center, hospital emergency room, or physician immediately.</p>
Note to Physician:	Call your local poison control center for further instructions.

5. FIRE FIGHTING MEASURES

Flash Pt:	NFPA Class-III A 152.60 F Method Used: TAG Closed Cup
Explosive Limits:	LEL: .8 UEL: 6
Autoignition Pt:	> 220.00 C
Suitable Extinguishing Media:	Use carbon dioxide, dry powder, or foam.
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
Flammable Properties and Hazards:	No data available.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	<p>Clean-up: Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources, keep flares, smoking or flames out of hazard area.</p> <p>Small spills: Take up the spilled liquid with sand, earth, or other noncombustible absorbent material and place in a plastic container where applicable.</p> <p>Large spills: Dike far ahead of spill for later disposal.</p>
---	---

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.
Precautions To Be Taken in Storing:	Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light distillate (petroleum)	No data.	TLV: 200 mg/m3	No data.
Respiratory Equipment (Specify Type):	When refueling, if possible, use outdoors in an open air area. If refueling indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- Stop -- ventilation is inadequate. Leave area immediately. Always follow appliance manufacturer's directions for fueling, ignition, and all other activities associated with use of the appliance.			
Eye Protection:	Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.			
Protective Gloves:	Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.			
Other Protective Clothing:	Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.			
Engineering Controls (Ventilation etc.):	Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering -- Stop -- ventilation is inadequate. Leave area immediately.			

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	Transparent, colorless.
Melting Point:	-49.00 C
Boiling Point:	192.00 C - 205.00 C
Autoignition Pt:	> 220.00 C
Flash Pt:	152.60 F Method Used: TAG Closed Cup
Explosive Limits:	LEL: .8 UEL: 6
Specific Gravity (Water = 1):	.79
Density:	6.59 LB/GL
Vapor Pressure (vs. Air or mm Hg):	.5 MM HG
Vapor Density (vs. Air = 1):	> 1 Air = 1
Evaporation Rate:	< 1 (BuAC=1)
Solubility in Water:	1.5 g/l
Percent Volatile:	100.0 % by weight.
VOC / Volume:	800.0000 G/L

Additional Physical Information Conductivity <50 picosiemens/meter

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability: No data available.

Incompatibility - Materials To Avoid: Incompatible with strong oxidizing agents.

Hazardous Decomposition Or Byproducts: Thermal decomposition may produce carbon monoxide and carbon dioxide.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Reactions: No data available.

11. TOXICOLOGICAL INFORMATION

Toxicological Information: In animal studies utilizing mineral spirits containing up to 22% aromatics indicated that the acute central nervous system effects are reversible. Based on existing animal studies, the potential for persistent effects is not clear. Distillates (petroleum), hydrotreated light: Mineral spirits have produced slight to moderate skin irritation particularly with evaporation from the skin is prevented. Animal studies have demonstrated that mineral spirits produced mild respiratory tract irritation at elevated concentrations.

Irritation or Corrosion: Primary dermal irritation studies (four hour exposure) in rabbits utilizing mineral spirits containing less than 2% aromatics resulted in slight to moderate skin irritation. In humans, mineral spirits have produced slight to moderate skin irritation particularly with evaporation from the skin is prevented. Animal studies have demonstrated that mineral spirits produced mild respiratory tract irritation at elevated concentrations. Also, sensory respiratory tract irritation was evident by reduced breathing rates in the test animals in certain studies.

Chronic Toxicological Effects: No known significant effects or critical hazards.

Carcinogenicity/Other Information: ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum)	n.a.	n.a.	A4	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: PETROLEUM DISTILLATES

DOT Hazard Class:

UN/NA Number:

Additional Transport Information: Exempt Combustible Liquid per 49 CFR 173.150(f)

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-47-8	Hydrotreated light distillate (petroleum)	No	No	No

This material meets the EPA Yes No Acute (immediate) Health Hazard

'Hazard Categories' defined Yes No Chronic (delayed) Health Hazard

for SARA Title III Sections Yes No Fire Hazard

311/312 as indicated: Yes No Sudden Release of Pressure Hazard

Yes No Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
64742-47-8	Hydrotreated light distillate (petroleum)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

16. OTHER INFORMATION

Revision Date: 05/01/2015

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About This Product: No data available.

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.