

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Ethyl acetate

Product Number : 270989  
Brand : Sigma-Aldrich

Supplier : Sigma-Aldrich  
3050 Spruce Street  
SAINT LOUIS MO 63103  
USA

Telephone : +1 800-325-5832  
Fax : +1 800-325-5052  
Emergency Phone # (For both supplier and manufacturer) : (314) 776-6555

Preparation Information : Sigma-Aldrich Corporation  
Product Safety - Americas Region  
1-800-521-8956

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

##### OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant

##### Target Organs

Blood, Kidney, Liver, Central nervous system

##### GHS Classification

Flammable liquids (Category 2)  
Acute toxicity, Inhalation (Category 5)  
Eye irritation (Category 2A)  
Specific target organ toxicity - single exposure (Category 3)

##### GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H333 May be harmful if inhaled.  
H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

##### HMIS Classification

Health hazard: 2  
Chronic Health Hazard: \*

**Flammability:** 3  
**Physical hazards:** 1

**NFPA Rating**

**Health hazard:** 2  
**Fire:** 3  
**Reactivity Hazard:** 1

**Potential Health Effects**

**Inhalation** May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness.  
**Skin** May be harmful if absorbed through skin. Causes skin irritation.  
**Eyes** Causes eye irritation.  
**Ingestion** May be harmful if swallowed.

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Formula : C<sub>4</sub>H<sub>8</sub>O<sub>2</sub>  
Molecular Weight : 88.11 g/mol

Component	Concentration
<b>Ethyl acetate</b>	
CAS-No. 141-78-6	-
EC-No. 205-500-4	
Index-No. 607-022-00-5	
Registration number 01-2119475103-46-XXXX	

---

**4. FIRST AID MEASURES**

**General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

**If inhaled**

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

**In case of skin contact**

Wash off with soap and plenty of water. Consult a physician.

**In case of eye contact**

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**If swallowed**

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

---

**5. FIREFIGHTING MEASURES**

**Conditions of flammability**

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

**Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**Special protective equipment for firefighters**

Wear self contained breathing apparatus for fire fighting if necessary.

**Hazardous combustion products**

Hazardous decomposition products formed under fire conditions. - Carbon oxides

**Further information**

Use water spray to cool unopened containers.

---

**6. ACCIDENTAL RELEASE MEASURES**

### Personal precautions

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

### Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

---

## 7. HANDLING AND STORAGE

### Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

### Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Ethyl acetate	141-78-6	TWA	400 ppm	USA. ACGIH Threshold Limit Values (TLV)
Remarks	Eye & Upper Respiratory Tract irritation			
		TWA	400 ppm 1,400 mg/m <sup>3</sup>	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	400 ppm 1,400 mg/m <sup>3</sup>	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	The value in mg/m <sup>3</sup> is approximate.			
		TWA	400 ppm 1,400 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits

### Personal protective equipment

#### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### Splash protection

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: > 30 min

Material tested: Butoject® (Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 873000, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an Industrial Hygienist familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Eye protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin and body protection**

impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

---

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

### **Appearance**

Form	clear, liquid
Colour	colourless

### **Safety data**

pH	no data available
Melting point/freezing point	Melting point/range: -84 °C (-119 °F)
Boiling point	76.5 - 77.5 °C (169.7 - 171.5 °F)
Flash point	-3.0 °C (26.6 °F) - closed cup
Ignition temperature	427 °C (801 °F)
Autoignition temperature	427.0 °C (800.6 °F)
Lower explosion limit	2.2 %(V)
Upper explosion limit	11.5 %(V)
Vapour pressure	97.3 hPa (73.0 mmHg) at 20.0 °C (68.0 °F)
Density	0.902 g/mL at 25 °C (77 °F)
Water solubility	soluble
Partition coefficient: n-octanol/water	log Pow: 0.73
Relative vapour density	no data available
Odour	no data available
Odour Threshold	no data available
Evaporation rate	no data available

---

## **10. STABILITY AND REACTIVITY**

### **Chemical stability**

Stable under recommended storage conditions.

### **Possibility of hazardous reactions**

Vapours may form explosive mixture with air.

**Conditions to avoid**

Heat, flames and sparks. Extremes of temperature and direct sunlight.

**Materials to avoid**

Strong oxidizing agents

**Hazardous decomposition products**

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - no data available

---

**11. TOXICOLOGICAL INFORMATION****Acute toxicity****Oral LD50**

LD50 Oral - rat - 5,620 mg/kg

**Inhalation LC50**

LC50 Inhalation - mouse - 2 h - 45,000 mg/m<sup>3</sup>

**Dermal LD50**

LD50 Dermal - rabbit - > 180,000 mg/kg

**Other information on acute toxicity**

no data available

**Skin corrosion/irritation**

no data available

**Serious eye damage/eye irritation**

no data available

**Respiratory or skin sensitization**

no data available

**Germ cell mutagenicity**

no data available

**Carcinogenicity**

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**Reproductive toxicity**

no data available

**Teratogenicity**

no data available

**Specific target organ toxicity - single exposure (Globally Harmonized System)**

May cause drowsiness or dizziness.

**Specific target organ toxicity - repeated exposure (Globally Harmonized System)**

no data available

**Aspiration hazard**

no data available

**Potential health effects**

**Inhalation** May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness.

**Ingestion** May be harmful if swallowed.

**Skin** May be harmful if absorbed through skin. Causes skin irritation.

**Eyes** Causes eye irritation.

**Signs and Symptoms of Exposure**

Central nervous system depression, Drowsiness, narcosis, anemia

**Synergistic effects**

no data available

**Additional Information**

RTECS: AH5425000

---

**12. ECOLOGICAL INFORMATION****Toxicity**

Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 350.00 - 600.00 mg/l - 96 h

LC50 - Pimephales promelas (fathead minnow) - 220.00 - 250.00 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates EC50 - Daphnia magna (Water flea) - 2,300.00 - 3,090.00 mg/l - 24 h

LC50 - Daphnia magna (Water flea) - 560 mg/l - 48 h

Toxicity to algae EC50 - Algae - 4,300.00 mg/l - 24 h

EC50 - SELENASTRUM - 1,800.00 - 3,200.00 mg/l - 72 h

**Persistence and degradability**

no data available

**Bioaccumulative potential**

no data available

**Mobility in soil**

no data available

**PBT and vPvB assessment**

no data available

**Other adverse effects**

no data available

---

**13. DISPOSAL CONSIDERATIONS****Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

**Contaminated packaging**

Dispose of as unused product.

## 14. TRANSPORT INFORMATION

### DOT (US)

UN number: 1173 Class: 3 Packing group: II  
Proper shipping name: Ethyl acetate  
Reportable Quantity (RQ): 5000 lbs  
Marine pollutant: No  
Poison Inhalation Hazard: No

### IMDG

UN number: 1173 Class: 3 Packing group: II EMS-No: F-E, S-D  
Proper shipping name: ETHYL ACETATE  
Marine pollutant: No

### IATA

UN number: 1173 Class: 3 Packing group: II  
Proper shipping name: Ethyl acetate

---

## 15. REGULATORY INFORMATION

### OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant

### SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

### Massachusetts Right To Know Components

	CAS-No.	Revision Date
Ethyl acetate	141-78-6	2007-03-01

### Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Ethyl acetate	141-78-6	2007-03-01

### New Jersey Right To Know Components

	CAS-No.	Revision Date
Ethyl acetate	141-78-6	2007-03-01

### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

---

## 16. OTHER INFORMATION

### Further information

Copyright 2012 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.