



Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name: **Hydraulic & Jack Oil**

Product Number (s): **SL2552, SL2553, SL2555, SL2621**

Manufactured By:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

General Information (215) 674-4300

Technical Assistance (800) 521-3168

Customer Service (800) 272-4620

24-Hr Emergency (CHEMTREC) (800) 424-9300

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Amber viscous liquid, faint petroleum odor

As defined by OSHA's Hazard Communication Standard, this product is non-hazardous.

Potential Health Effects:

EYE: Direct contact may cause irritation and redness.

SKIN: Slightly irritating. Repeated or prolonged contact can result in drying of the skin.

INHALATION: Oil mist can irritate the airways and lungs.

INGESTION: May cause stomach pain or vomiting. Main hazard, if ingested, is aspiration into the lungs and subsequent pneumonitis.

CHRONIC EFFECTS: Unknown

TARGET ORGANS: Unknown

Medical Conditions Aggravated by Exposure:

Unknown

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: Hydraulic & Jack Oil

Product Number (s): SL2552, SL2553, SL2555, SL2621

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Hydrotreated heavy paraffinic distillates	64742-54-7	50 – 70
Solvent-refined heavy naphthenic distillates	64741-96-4	30 – 50
Zinc, dithiophosphate di-C1-14-alkyl esters	68649-42-3	0.2 - 1

Section 4: First Aid Measures

- Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
- Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
- Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
- Ingestion:** Do NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

Note to Physicians: Treat symptomatically.

Section 5: Fire-Fighting Measures

Flammable Properties: As defined by OSHA, this product is nonflammable.

Flash Point:	280 F (COC)	Upper Explosive Limit:	ND
Autoignition Temperature:	ND	Lower Explosive Limit:	ND

Suitable Extinguishing Media: Foam, dry chemicals, sand, dolomite, carbon dioxide

Products of Combustion: Acrid smoke/fumes. Oxides of carbon.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. Volume and pressure of material increases strongly when heated.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8. Minimize skin contact. Avoid breathing vapors.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Product Name: Hydraulic & Jack Oil

Product Number (s): SL2552, SL2553, SL2555, SL2621

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Do not reuse container. Keep container closed when not in use. Ventilate well and avoid breathing vapors. Do not store or mix with strong oxidizers. Avoid strong heating. Keep away from sparks and open flame.

Storage Procedures: Store in a cool dry area out of direct sunlight. Keep away from sources of ignition. Store away from strong acids and oxidizers.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Hydrotreated heavy paraffinic distillates	5	NE	5	NE	NE		mg/m ³
Solvent-refined heavy naphthenic distillates	5	NE	5	NE	NE		mg/m ³
Zinc, dithiophosphate di-C1-14-alkyl esters	NE	NE	NE	NE	NE		
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Engineering Controls: Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use a NIOSH-approved cartridge respirator with organic vapor cartridges if vapors exceed exposure limits. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as Nitrile or PVC. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Product Name: Hydraulic & Jack Oil
Product Number (s): SL2552, SL2553, SL2555, SL2621

Section 9: Physical and Chemical Properties

Physical State: liquid (viscous)
Color: Amber
Odor: Mild petroleum
Specific Gravity: 0.90
Initial Boiling Point: > 350 F
Freezing Point: ND
Vapor Pressure: < 0.1 mmHg @ 68F
Vapor Density: > 5 (air = 1)
Evaporation Rate: < 0.01 (butyl acetate = 1)
Solubility: Insoluble in water
pH: NA
Volatile Organic Compounds: wt %: 0 g/L: 0 lbs./gal: 0

Section 10: Stability and Reactivity

Stability: Stable
Conditions to Avoid: Sources of ignition, heat
Incompatible Materials: Strong acids and oxidizers
Hazardous Decomposition Products: Oxides of carbon, sulfur and phosphorus
Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

<u>Component</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Hydrotreated heavy paraffinic distillates	LD50	> 5000 mg/kg	Oral	Rat
Hydrotreated heavy paraffinic distillates	LC50	2.4 mg/L/4H	Inhalation	Rat
Hydrotreated heavy paraffinic distillates	LD50	> 2000 mg/kg	Dermal	Rabbit

CHRONIC EFFECTS

Carcinogenicity:

	<u>Component</u>	<u>Result</u>
OSHA:	None listed	
IARC:	None listed	
NTP:	None listed	

Mutagenicity: No information available

Other: IARC has determined in reviewing cancer prevalence of exposed workers that the carcinogenic

Product Name: Hydraulic & Jack Oil

Product Number (s): SL2552, SL2553, SL2555, SL2621

activity of refined oils is related to the severity of processing of the base oil. The base oils in this product contain < 3% DMSO Extractable total polycyclic aromatic compound (PAC) per IP 346.

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:	No information available
Persistence / Degradability:	No information available
Bioaccumulation / Accumulation:	No information available
Mobility in Environment:	No information available

Section 13: Disposal Considerations

Disposal: This product is not a RCRA hazardous waste as packaged. (See 40 CFR Part 261.20 – 261.33)
Used oil should be collected and handled in accordance with 40 CFR Part 279. Used oil that is mixed with hazardous waste may be subject to regulation as hazardous waste.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Section 14: Transport Information

Proper shipping description:

JS DOT (ground): Not regulated.

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	No
	Reactive Hazard	No
	Release of Pressure	No
	Acute Health Hazard	No
	Chronic Health Hazard	No

Product Name: Hydraulic & Jack Oil

Product Number (s): SL2552, SL2553, SL2555, SL2621

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

Zinc, dithiophosphate di-C1-14-alkyl esters (zinc compounds): < 1%

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

State Regulations

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

N-Methylpyrrolidone (< 35 ppm)
cadmium (< 1 ppm)

State Right to Know:

New Jersey: 68649-42-3, 64742-54-7
Pennsylvania: 68649-42-3
Massachusetts: 64742-54-7
Rhode Island : None

Additional Regulatory Information: None

Section 16: Other Information

NFPA: Health: 1 Flammability: 1 Reactivity: 0
HMIS: Health: 1 Flammability: 1 Reactivity: 0 PPE: B

Prepared By: Michelle Rudnick
CRC #: 720150
Revision Date: 10/11/2012

Changes since last revision: Revision date

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
PMCC:	Pensky-Martens Closed Cup	g/L:	grams per Liter
PPE:	Personal Protection Equipment	lbs./gal:	pounds per gallon
TWA:	Time Weighted Average	STEL:	Short Term Exposure Limit
OSHA:	Occupational Safety and Health Administration	COC:	Cleveland Open Cup
CGIH:	American Association of Governmental Industrial Hygienists		
NIOSH:	National Institute of Occupational Safety & Health		